

Yeastar NeoGate TA Analog Gateways



NeaGate TA Analog VoIP Gateways הנה סדרת מוצרים חדשנית המאפשרת חיבור טלפונים אנלוגיים או מכשירי פקס עם מערכות המבוססות IP PBX מהדור החדש. המוצרים מתאפיינים בפונקציונאליות גבוהה, התקנה פשוטה וקלות תפעולית. קו מוצרים זה הינו אידיאלי עבור עסקיים קטנים ובינוניים המעוניינים בשילוב מערכת טלפוניה מסורתית אנלוגית לתוך מערכת חדשנית מבוססת IP ובכך תורמים בשמירת ההשקעה הקודמת ויחד עם זאת בהפחתת עלויות התקשורת תוך ניצול טכנולוגיית ה VOIP.

תכונות עיקריות

- ❖ FXS מבואות 4/8/16/24/32
- ❖ תאימות מלאה ל SIP ול IAX2
- ❖ כללי חיוג גמישים
- ❖ תמיכה בשיגור פקסים באמצעות פרוטוקול T.38
- ❖ דחיסת קול באיכות גבוהה
- ❖ ביטול הד (8, 16, 32, 64 or 128 ms echo delays)
- ❖ ממשק משתמש קל להגדרה וניהול
- ❖ תמיכה בניטור ובניהול תצורה דרך פרוטוקול TR069
- ❖ תאימות ואמינות מוכחות בהתקנות מרובות

Items	TA400	TA800	TA1600	TA2400	TA3200
RJ11 FXS Ports	4	8	16	24	32
RJ21 FXS Ports	-	-	1	1	2
LAN	1	1	1	1	1
Codecs	G.711 (a-law/u-law), G.722,G.723, G.726, G.729A, GSM, ADPCM				
Media Processing	ITU-T G.168 Echo Cancellation, Dynamic Jitter Buffer, VAD, CNG, PLC				
Fax	T.38 and Pass-through				
Protocols	SIP, IAX2				
DTMF	RFC2833, SIP info, In-band				
Transport	UDP, TCP, TLS, SRTP				
Firewall	Built-in Firewall, IP Blacklist, Attack Alert				
Network	FTP, TFTP, HTTP, HTTPS, SSH				
Management	Web GUI, Auto provisioning, Backup and Restore, System logs				
Mounting	Desktop, Wall-mount		Desktop, Rack Mount		
	200 (L) X 137 (W) X 25.6 (H)		440(L) X 250 (W) X 44 (H)		

Interoperability

